

## H series SOLAR LED STREET LIGHT QUOTATION SHEET

Item	Q'ty	Unit price	Parameters		Size & Packages
 <b>LAL-SSL-30WH</b>	<100pcs	\$221.66	30W Solar LED street light	Battery: Grade A Lithium 3.2V/24AH	Lamp size: 575*405*140mm 1pc/ CTN; Carton Size: 52*43*22Cm Gross Weight: 7KG
	<300pcs	\$217.64	Material: Aluminum Alloy	Charge time: 6-7 hours(by Sun)	
	<1000pcs	\$215.62	Solar Panel: 6V / 25W Monocrystalline	Working time: 12 hrs & 3-5 rain days	
	>1000pcs	\$213.60	LEDs: High Lumens Lumileds SMD3030	Installation height: 3-5M, Pole diameter:50-60mm .	
			Lumen efficiency: 180-200Lm/W	IK09, IP67 waterprof	
			Operation modes: Time control / Induction control / Time + induction control		
 <b>LAL-SSL-40WH</b>	<100pcs	\$263.66	40W Solar LED street light	Battery: Grade A Lithium 12V / 12 AH	Lamp size: 735*405*140mm 1pc/ CTN; Carton Size: 68*43*22Cm Gross Weight: 9.5KG
	<300pcs	\$258.88	Material: Aluminum Alloy	Charge time: 6-7 hours(by Sun)	
	<1000pcs	\$256.48	Solar Panel: 18V / 35W Monocrystalline	Working time: 12 hrs & 3-5 rain days	
	>1000pcs	\$254.08	LEDs: High Lumens Lumileds SMD3030	Installation height: 4-6M, Pole diameter:50-60mm .	
			Lumen efficiency: 180-200Lm/W	IK09, IP67 waterprof	
			Operation modes: Time control / Induction control / Time + induction control		
 <b>LAL-SSL-60WH</b>	<100pcs	\$326.00	60W Solar LED street light	Battery: Grade A Lithium 12V / 16AH	Lamp size: 905*405*140mm 1pc/ CTN; Carton Size: 85*43*22Cm Gross Weight: 13.5KG
	<300pcs	\$320.08	Material: Aluminum Alloy	Charge time: 6-7 hours(by Sun)	
	<1000pcs	\$317.10	Solar Panel: 18V / 50W Monocrystalline	Working time: 12 hrs & 3-5 rain days	
	>1000pcs	\$314.14	LEDs: High Lumens Lumileds SMD3030	Installation height: 5-6M, Pole diameter:50-60mm	
			Lumen efficiency: 180-200Lm/W	. IK09, IP67 waterprof	
			Operation modes: Time control / Induction control / Time + induction control		
 <b>LAL-SSL-80WH</b>	<100pcs	\$383.00	80W Solar LED street light	Battery: Grade A Lithium 12V / 20AH	Lamp size: 1290*360*90mm 1pc/ CTN; Carton Size: 146*43*22Cm Gross Weight: 17KG
	<300pcs	\$376.04	Material: Aluminum Alloy	Charge time: 6-7 hours(by Sun)	
	<1000pcs	\$372.56	Solar Panel: 18V / 60W Monocrystalline	Working time: 12 hrs & 3-5 rain days	
	>1000pcs	\$369.08	LEDs: High Lumens Lumileds SMD3030	Installation height: 6-7M, Pole diameter:50-60mm .	
			Lumen efficiency: 180-200Lm/W	IK09, IP67 waterprof	
			Operation modes: Time control / Induction control / Time + induction control		
 <b>LAL-SSL-100WH</b>	<100pcs	\$485.66	100W Solar LED street light	Battery: Grade A Lithium 12V/30AH	Lamp size: 1290*360*90mm 1pc/ CTN; Carton Size: 146*43*22Cm Gross Weight: 20KG
	<300pcs	\$476.84	Material: Aluminum Alloy	Charge time: 6-7 hours(by Sun)	
	<500pcs	\$472.42	Solar Panel: 18V / 75W Monocrystalline	Working time: 12 hrs & 3-5 rain days	
	>1000pcs	\$468.00	LEDs: High Lumens Lumileds SMD3030	Installation height: 7-8M, Pole diameter:50-60mm .	
			Lumen efficiency: 180-200Lm/W	IK09, IP67 waterprof	
			Operation modes: Time control / Induction control / Time + induction control		
 <b>LAL-SSL-120WH</b>	<100pcs	\$707.34	120W Solar LED street light	Battery: Grade A Lithium 25.6V/22AH	Lamp size: 1290*520*160mm 1pc/ CTN; Carton Size: 137*54*23Cm Gross Weight: 24KG
	<300pcs	\$694.48	Material: Aluminum Alloy	Charge time: 6-7 hours(by Sun)	
	<1000pcs	\$688.04	Solar Panel: 36V / 120W Monocrystalline	Working time: 12 hrs & 3-5 rain days Installation	
	>1000pcs	\$681.62	LEDs: High Lumens Lumileds SMD5050	height: 8-10M, Pole diameter:50-60mm . IK09,	
			Lumen efficiency: 180-200Lm/W	IP67 waterprof	
			Operation modes: Time control		
 <b>LAL-SSL-150WH</b>	<100pcs	\$852.34	150W Solar LED street light	Battery: Grade A Lithium 25.6V/28AH	Lamp size: 1620*520*160mm 1pc/ CTN; Carton Size: 170*54*23Cm Gross Weight: 30KG
	<300pcs	\$836.84	Material: Aluminum Alloy	Charge time: 6-7 hours(by Sun)	
	<1000pcs	\$829.08	Solar Panel: 36V / 150W Monocrystalline	Working time: 12 hrs & 3-5 rain days	
	>1000pcs	\$821.34	LEDs: High Lumens Lumileds SMD5050	Installation height: 10-12M, Pole diameter:50-60mm	
			Lumen efficiency: 180-200Lm/W	. IK09, IP67 waterprof	
			Operation modes: Time control		

1, CCT: warm white:2700K / 3000K; Natural white:4000K Day white: 5000K; Cool white: 5700K / 6500K;

2, Payment terms: PAYPAL,Western Union, T/T, Money Gram. 40% deposit,60% balance before shipping;

3, Unit price is based on EX work, lead time: samples 5-7 days, bulk order: 7-15 days; Shipping way: Express,Air, Sea option, Clients's own shipping;

4, CE, 2 years warranty.

## Features

- 1) Smart control with PIR sensor; Without any electricity and wires;
- 2) Long lasting: 3 working days without sunshine;
- 3) High lumens efficiency reach 180-200Lm/W;
- 4) High efficiency imported silicon solar cell;
- 5) High performance Lithium battery ;



Press the on/off button to activate the fixture.



Fasten the screws to finish the installation on the pole.




When the light is above 10lux, it will turn off the light automatically, solar panel starts to charge.




1. Light switch auto-off for sun charging in daytime



2. It will gradually auto turn on bright at night



3. Sensor working distance is from 7 to 10 meters, when people get near, the lamp will automatically become brighter



4. When people walk away 5-8m, the lamp will automatically dim back to former brightness

