



SOLUTION PROVIDER  
for HIGH POWER LED  
LIGHT



## Ledalot LLC

### International Finance Center

Address: Level 54, Guangzhou IFC, 5 West Zhujiang Road,  
Suite 5409, Zhujiang New Town

Mobile / Whatsapp: +86 20 2801 6100


Email: [cetillit@ledalot.com](mailto:cetillit@ledalot.com)

[www.ledalot.com](http://www.ledalot.com)

[www.ledalot.com](http://www.ledalot.com)

.2025.

ST-Series  
Light Distribution Curve



ST-series features



ST100-1440W




ST-series items


Item No.	LAL-ST-1440W	LAL-ST-1200W	LAL-ST-960W LAL-ST-800W	LAL-ST-720WB LAL-ST-600WB	LAL-ST-480WB LAL-ST-400WB	LAL-ST-300WA	LAL-ST-240W / 200WA	LAL-ST-120W / 100WA
Power	1440W	1200W	960W/800W	720W / 600W	480W / 400W	300W	240W/200W	120W/100W
Input Voltage	100-277V / 180-528VAC 50/60Hz							
Beam angle	20° / 40° / 60° / 90° / 120° / 100*140° / P50							
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K							
Dim	1-10V / Dali / PWM dimmable							
Surge Protection	SPD 20KV/10KV/6KV/4KV							
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD5050 / CREE XTE; Ra70/Ra80/Ra90							
Materials	Fin aluminum heat sink + Optical Lens							
Light efficiency	150-160Lm/W							
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty							
Net Weight	28.38Kg	22.85Kg	19.62Kg	13.19Kg	9.3Kg	6.72Kg	5.63Kg	2.41Kg

ST-series application


Indoor outdoor stadium, sport field courts, play ground, highway, high mast, airport, seaport, ,park, square, tunnel, light tower, security.



ST-Rotating Series  
Light Distribution Curve



ST-series features



ST600-1440WU




ST-series items ▼


Item No.	LAL-ST-1440WU	LAL-ST-1200WU LAL-ST-1000WU	LAL-ST-960WU LAL-ST-800WU	LAL-ST-720WU LAL-ST-600WU
Power	1440W	1200W / 1000W	960W / 800W	720W / 600W
Input Voltage	100-277V / 180-528VAC 50/60Hz			
Beam angle	20° / 40° / 60° / 90° / 120° / 100*140° / P50			
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K			
Dim	1-10V / Dali / PWM dimmable			
Surge Protection	SPD 20KV/10KV/6KV/4KV			
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD5050 / CREE XTE; Ra70/Ra80/Ra90			
Materials	Fin aluminum heat sink + Optical Lens			
Light efficiency	150-160Lm/W			
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty			

ST-series application ▼

Indoor outdoor stadium, sport field courts, play ground, highway, high mast, airport, seaport, ,park, square, tunnel, security.



### FR- Series Light Distribution Curve



### FR-series application

Indoor outdoor stadium, sport field, play ground, highway, high mast, airport, seaport, park, square, tunnel, landscape.



### FR300-1600W



### FR-series items

Item No.	LAL-FR-1600W	LAL-FR-1000W	LAL-FR-600W	LAL-FR-500W	LAL-FR-400W	LAL-FR-300W
Power	1600W	100W	600W	500W	400W	300W
Input Voltage	100-277V / 180-528VAC 50/60Hz					
Beam angle	30° / 45° / 60° / 90°					
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K					
Dim	0-10V / Dali dimmable					
Surge Protection	SPD 20KV/10KV/6KV/4KV					
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD5050 ; Ra70/Ra80/Ra90					
Materials	Die casting aluminum heat sink + Optical PC Lens					
Light efficiency	150Lm/W				170Lm/W	
Spec.	Working temperature : -30° C --50° C / IP66 Waterproof / IK09 / 50,000Hrs Lifespan / 5 years warranty					

### FR-series Features



**Laser Sight**  
Easily adjust the direction of illumination to achieve maximum lux and uniformity.




**Visor**  
Minimizing glare light and spill light.



**HD TV Broadcasting**  
The LED source has a high TLCI index and a chromatic render index up to 90. This provides the camera with the real color of the scene and flicker-free shooting.



**IP66 Waterproof**  
**10/20kv Surge Protection**




**Precise Angle Rotation**



**Driver External**  
Driver box can be fixed on bracket or on pole in order to lower the weight of whole fixture and easy maintenance.

### ST-H Series Light Distribution Curve



### ST300-1500WH



#### ST-series items


Item No.	LAL-ST-1500WH	LAL-ST-1000WH	LAL-ST-900WH	LAL-ST-600WH	LAL-ST-500WH	LAL-ST-300WH
Power	1500W	1000W	900W	600W	500W	300W
Input Voltage	100-277V / 180-528VAC 50/60Hz					
Beam angle	20° / 40° / 60° / 90° / P50 Asymmetric					
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K					
Dim	1-10V / Dali / PWM dimmable by DALI/Zigbee /DMX control					
Surge Protection	SPD 20KV/10KV/6KV/4KV					
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD5050/ 3030; Ra70/Ra80/Ra90					
Materials	Fin aluminum heat sink + Optical Lens + Reflector					
Light efficiency	160Lm/W					
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty					
Net Weight	29Kg	22.51Kg	28.12Kg	18.6Kg	9.97Kg	9.63Kg

#### ST-H series application

Indoor outdoor stadium, sport field courts, play ground, highway, high mast, airport, seaport, park, square, tunnel.




### ST-G Series Light Distribution Curve



### 1 DALI Dimming System Total Solution

### 2 DMX Dimming System Total Solution



### Accessories



### ST100-1440WG




### ST-series items


Item No.	LAL-ST-1440WG	LAL-ST-1200WG	LAL-ST-960WG LAL-ST-800WG	LAL-ST-720WG LAL-ST-600WG	LAL-ST-480WG LAL-ST-400WG	LAL-ST-240WG LAL-ST-200WG
Power	1440W	1200W	960W/800W	720W / 600W	480W / 400W	240W/200W
Input Voltage	100-277V / 180-528VAC 50/60Hz					
Beam angle	20° / 40° / 60° / 90° / 120° / 100*140° / P50 Asymmetric					
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K					
Dim	1-10V / Dali / PWM dimmable by DALI/Zigbee /DMX control					
Surge Protection	SPD 20KV/10KV/6KV/4KV					
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD5050/ 3030; Ra70/Ra80/Ra90					
Materials	Fin aluminum heat sink + Optical Lens + Reflector					
Light efficiency	150-160lm/W					
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty					
Net Weight	25.67Kg	20.81Kg	17.73Kg	11.87Kg	8.02Kg	4.32Kg

### ST-G series application

Indoor outdoor stadium, sport field courts, play ground, highway, high mast, airport, seaport, ,park, square, tunnel



TL-C Series  
Light Distribution Curve



Accessories



TL100-600WC




ST-series items ▼


Item No.	LAL-TL-600WC	LAL-TL-500WC	LAL-TL-400WC	LAL-TL-300WC	LAL-TL-200WC	LAL-TL-100WC
Power	600W	500W	400W	300W	200W	100W
Input Voltage	100-277V / 180-528VAC 50/60Hz					
Beam angle	20° / 40° / 60° / 90°					
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K					
Dim	1-10V / Dali / PWM dimmable by DALI/Zigbee /DMX control					
Surge Protection	SPD 20KV/10KV/6KV/4KV					
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD5050/ 3030; Ra70/Ra80/Ra90					
Materials	Fin aluminum heat sink + Optical Lens + Reflector					
Light efficiency	150Lm/W					
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty					
Net Weight	12.03Kg	9.55Kg	8.96Kg	6..21Kg	5.43Kg	2.3Kg

TL-C series application ▼


Indoor outdoor stadium, sport field courts, play ground, highway, high mast, airport, seaport, ,park, square, tunnel



C LED Flood light  
Series Light  
Distribution Curve



C-series features



ST400-1000WC



C series items


Item No.	LAL-ST-1000WC	LAL-ST-750WC	LAL-ST-600WC	LAL-ST-500WC	LAL-ST-400WC
Power	1000W	750W	600W	500W	400W
Input Voltage	100-277V / 180-528VAC 50/60Hz				
Beam angle	15° / 30° / 60° / 90° / P6				
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K				
Dim	1-10V / Dali / PWM / DMX dimmable				
SPD	SPD 20KV/10KV/6KV/4KV				
Driver /LEDs	Meanwell / Sosen / Inventronics ; SMD2835; Ra70/Ra80/Ra90				
Materials	ADC12 Die casting aluminum heat sink + PC lens				
Light efficiency	160-180Lm/W				
Spec.	Working temperature : -30° C --50° C / IP66 / IK09 / 50,000Hrs Lifespan / CE RoHS / 5 years warranty				
Net Weight	11.8Kg	10.3Kg	10.3Kg	9.1Kg	8.9Kg

C-series application

Indoor outdoor sport field courts, play grounds, highway, high mast, airport, seaport, ,park, square, tunnel, advertising board, landscape.



C LED Flood light  
Series Light  
Distribution Curve



### ST50-250WC



C series items ▼


Item No.	LAL-ST-250WC	LAL-ST-200WC	LAL-ST-180WC	LAL-ST-150WC	LAL-ST-120WC	LAL-ST-100WC	LAL-ST-50WC LAL-ST-60WC
Power	250W	200W	180W	150W	120W	100W	50W/60W
Input Voltage	100-277V / 180-528VAC 50/60Hz						
Beam angle	15° / 30° / 60° / 90°						
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K						
Dim	1-10V / Dali / PWM / DMX dimmable						
SPD	SPD 20KV/10KV/6KV/4KV						
Driver /LEDs	Meanwell / Sosen / Inventronics ; SMD2835; Ra70/Ra80/Ra90						
Materials	ADC12 Die casting aluminum heat sink + PC lens						
Light efficiency	160-180Lm/W						
Spec.	Working temperature : -30° C --50° C / IP66 / IK09 / 50,000Hrs Lifespan / CE RoHS / 5 years warranty						
Net Weight	3.6Kg	3.6Kg	3.2Kg	3.2Kg	3Kg	3Kg	2.3Kg

C -series features




C -series application ▼

Indoor outdoor sport field courts, play grounds, highway, high mast, airport, seaport, ,park, square, tunnel, advertising board, landscape.



### ST-E Series Light Distribution Curve



### ST100-1440WD



#### ST-series items

Item No.	LAL-ST-1500WE	LAL-ST-1200WE	LAL-ST-900WE	LAL-ST-600WE	LAL-ST-300WE
Power	1500W	1200W	900W	600W	300W
Input Voltage	100-277V / 180-528VAC 50/60Hz				
Beam angle	10° / 20° / 40° / 60° / P50				
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K				
Dim	1-10V / Dali / PWM dimmable				
Surge Protection	SPD 20KV/10KV/6KV/4KV				
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD5050 / CREE XTE; Ra70/Ra80/Ra90				
Materials	Fin aluminum heat sink + Optical Lens				
Light efficiency	160Lm/W				
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty				
Net Weight	21Kg	16.36Kg	14.75Kg	9.03Kg	6.31Kg

#### ST-E series features

**Heat dissipation**

1. Light weight, easy installation
2. Folding Fin aluminum design
3. Expand heat dissipation area

**Waterproof**

IP66 waterproof  
Safer outdoor use

**High efficiency**


1. 160-190Lm/W
2. Lumiled SMD5050

**Anti glare**

Lampshades for Anti glare



#### ST-E series application

Indoor outdoor stadium, sport field courts, play ground, highway, high mast, airport, seaport, park, square, tunnel.



**FREE**  
Dialux Lighting Design

### FL-Series Light Distribution Curve



### FL400-1800W




#### FL-series items


Item No.	LAL-FL-2000WH	LAL-FL-1500WH	LAL-FL-1000WH	LAL-FL-500WH
Power	2000W	1500W	1000W	500W
Input Voltage	100-277V / 180-528VAC 50/60Hz			
Beam angle	15° / 30° / 60 / 90° / 120° / P50 / T2 / T3 / T4			
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K			
Dim	0-10V / Dali / PWM dimmable			
Surge Protection	SPD 20KV/10KV/6KV/4KV			
Driver / LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD5050; Ra70/Ra80/Ra90			
Materials	Die casting Aluminum heat sink + Optical Lens +Tempered Glass			
Size(mm)	762*966*122	762*736*122	762*504*122	L762*273*122
Light efficiency	150Lm/W; 170Lm/W			
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / IK08 / 50,000Hrs Lifespan / 5 years warranty			

#### FL-series application



Indoor outdoor stadium, sport field courts, play ground, highway, high mast, airport, seaport, ,park, square, tunnel, light tower, security.



### TL-3 Series Light Distribution Curve



### Installations & Parts



### TL100-1000W-3



### TL series items



Item No.	LAL-TL-1000W3	LAL-TL-800W3	LAL-TL-600W3	LAL-TL-500W3	LAL-TL-400W3	LAL-TL-300W3	LAL-TL-200W3	LAL-TL-100W3
Power	1000W	800W	600W	500W	400W	300W	200W	100W
Input Voltage	100-277V / 180-528VAC 50/60Hz							
Beam angle	30° / 60° / 90°							
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K							
Dim	1-10V / Dali / PWM dimmable							
SPD	SPD 20KV/10KV/6KV/4KV							
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD5050; Ra70/Ra80/Ra90							
Materials	Die casting aluminum heat sink + Optical PC Lens							
Light efficiency	140Lm/W							
Spec.	Working temperature : -30° C --50° C / IP66 Waterproof / IK09. / 50,000Hrs Lifespan / 5 years warranty							

### TL-3 series application

Indoor outdoor stadium, sport field courts, play ground, highway, high mast, airport, seaport, ,park, square, tunnel, light tower, security.



Slim LED Flood Light Series Light Distribution Curve



FL30-600WK



FL series items


Item No.	LAL-FL-600WK	LAL-FL-500WK	LAL-FL-400WK	LAL-FL-300W/240WK	LAL-FL-200WK	LAL-FL-150WK	LAL-FL-100WK	LAL-FL-50WK	LAL-FL-30WK
Power	600W	500W	400W	300W/240W	200W	150W	100W	50W	30W
Input Voltage	100-277V / 180-528VAC 50/60Hz								
Beam angle	15° /30° /60° /90° /120° /T2/T3/60*120° /30*90° (P50)								
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K								
Dim	0-10V / Dali / PWM dimmable								
SPD	SPD 20KV/10KV/6KV								
Driver /LEDs	PF: >0.9/Meanwell / Sosen / Moso/ Done/ Philips; SMD3030/2835; Ra70/80								
Materials	Die aluminum heat sink + Tempered glass + Anti UV PC lens								
Light efficiency	150m/W; 170Lm/W								
Spec.	Working temperature : -30° C --50° C / IP66 Waterproof / IK08 // 50,000Hrs Lifespan / 5 years warranty								
Net Weight	12Kg	10.8Kg	8Kg	5.3Kg	3.5Kg	3.2Kg	2.3Kg	1.5Kg	1.3

FL-series application

Indoor outdoor sport field courts, playground, highway, high mast, airport, seaport, park, square, advertising board, landscape.





Slim FL Series Light Distribution Curve



120°

Installations



FL10-400WC






FL series items


Item No.	LAL-FL-400WC	LAL-FL-300WC	LAL-FL-200WC	LAL-FL-150WC	LAL-FL-100WC	LAL-FL-50WC	LAL-FL-30WC	LAL-FL-20WC	LAL-FL-10WC
Power	400W	300W	200W	150W	100W	50W	30W	20W	10W
Input Voltage	200-265V / 120VAC 50/60Hz								
Beam angle	120°								
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K								
Sensor	PIR Sensor								
CRI	Ra80								
Driver /LEDs	IC Dirver / Epistar SMD2835								
Materials	Die aluminum heat sink + Tempered Glass								
Light efficiency	100Lm/W								
Spec.	Working temperature : -30° C --45° C / IP66 Waterproof / 50,000Hrs Lifespan / 3 years warranty								

FL-series application

Indoor outdoor sport field courts, play ground, highway, high mast, airport, seaport, ,park, square, advertising board, landscape.



### ST-Series Light Distribution Curve



### ST100-1440WD



### ST-series items

Item No.	LAL-ST-1440W	LAL-ST-1200WD	LAL-ST-960WD LAL-ST-800WD	LAL-ST-720WD LAL-ST-600WD	LAL-ST-480WD LAL-ST-400WD
Power	1440W	1200W	960W / 800W	720W / 600W	480W / 400W
Input Voltage	100-277V / 180-528VAC 50/60Hz				
Beam angle	10° / 20° / 40° / 60° / P50				
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K				
Dim	1-10V / Dali / PWM dimmable				
Surge Protection	SPD 20KV/10KV/6KV/4KV				
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD5050 / CREE XTE; Ra70/Ra80/Ra90				
Materials	Fin aluminum heat sink + Optical Lens				
Light efficiency	150-160Lm/W				
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty				
Net Weight	21Kg	16.36Kg	14.92Kg	8.86Kg	7.37Kg

### ST-series features

**Anti glare**  
Lampshades for Anti glare

**Heat dissipation**

1. Light weight, easy installation
2. Folding Fin aluminum design
3. Expand heat dissipation area


**High efficiency**

1. 160Lm/W
2. Lumiled SMD5050


**Waterproof**  
IP66 waterproof  
Safer outdoor use

### ST-series application

Indoor outdoor stadium, sport field courts, play ground, highway, high mast, airport, seaport, ,park, square, tunnel



### ST-Series Light Distribution Curve



### ST-series features

**Anti glare**  
Lampshades for Anti glare

**Heat dissipation**

1. Light weight, easy installation
2. Folding Fin aluminum design
3. Expand heat dissipation area

**High efficiency**

1. 160Lm/W
2. Lumiled SMD5050

**Waterproof**  
IP66 waterproof  
Safer outdoor use

### ST200-720WC



### ST-series items


Item No.	LAL-ST-720WC	LAL-ST-600WC	LAL-ST-480WC LAL-ST-400WC	LAL-ST-300WC	LAL-ST-240WC LAL-ST-200WC
Power	720W	600W	480W / 400W	300W	240W / 200W
Input Voltage	100-277V / 180-528VAC 50/60Hz				
Beam angle	20° / 40° / 60° / 90° / 120° / 100*140° / P50				
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K				
Dim	1-10V / Dali / PWM dimmable				
Surge Protection	SPD 20KV/10KV/6KV/4KV				
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD5050 / CREE XTE; Ra70/Ra80/Ra90				
Materials	Fin aluminum heat sink + Optical Lens				
Light efficiency	150-160Lm/W				
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty				
Net Weight	13.12Kg	11.97Kg	8.75Kg	6.81Kg	2.83Kg

### ST-series application


Indoor outdoor stadium, sport field courts, playground, highway, high mast, airport, seaport, ,park, square, tunnel, security.



### TL-D Series Light Distribution Curve



60°




90°

### TL-series features

#### Casting aluminum housing

Die casting aluminum design for best heat sink, IK10



#### Excellent Appearance

Modular & streamline design



### TL50-1000W



#### TL series items


Item No.	LAL-TL-1000W	LAL-TL-800W	LAL-TL-600W	LAL-TL-500W	LAL-TL-400W	LAL-TL-300W	LAL-TL-240W	LAL-TL-200W	LAL-TL-150W	LAL-TL-100W	LAL-TL-50W
Power	1000W	800W	600W	500W	400W	300W	240W	200W	150W	100W	50W
Input Voltage	100-277V / 180-528VAC 50/60Hz										
Beam angle	60° / 90° / 120°										
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K										
Dim	1-10V / Dali / PWM dimmable										
SPD	SPD 20KV/10KV/6KV/4KV										
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90										
Materials	Extruded aluminum heat sink										
Light efficiency	140Lm/W										
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty										
Net Weight	19.16 Kg	17.28 Kg	12.02 Kg	10.71 Kg	8.64Kg	6.01Kg	5.39Kg	4.32Kg	3.25Kg	2.31Kg	1.98Kg

#### TL-series application


Indoor outdoor sport field courts, play ground, highway, high mast, airport, seaport, ,park, square, tunnel, road, advertising board, landscape.



### TL-S Series Light Distribution Curve



### TL-S series Features



### TL50W-600WS



### TL-D series items

Item No.	LAL-TL-600WS	LAL-TL-500WS	LAL-TL-400WS	LAL-TL-300WS	LAL-TL-240WS	LAL-TL-200WS	LAL-TL-150WS	LAL-TL-100WS	LAL-TL-50WS
Power	600W	500W	400W	300W	240W	200W	150W	100W	50W
Input Voltage	100-277V / 180-528VAC 50/60Hz								
Beam angle	30° / 60° / 90° / 120° / P50 / T2/T3/T4								
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K								
Dim	1-10V / Dali / PWM dimmable								
SPD	SPD 20KV/10KV/6KV/4KV								
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90								
Materials	Die casting Aluminum Heat Sink + Optics Lens + Tempered Glass								
Light efficiency	Lumileds SMD3030 140Lm/W; SMD5050 160LM/W								
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty								
Net Weight	17.5 Kg	15.2 Kg	12.9Kg	9.3Kg	7.9Kg	6.8Kg	5.7Kg	4.5Kg	3.35Kg

### TL-series application

Indoor outdoor sport field courts, play ground, highway, high mast, airport, seaport, ,park, square, tunnel, road, advertising board, landscape.




### L2 LED street light Series



ZHAGA standard extension receptacle and cap      NEMA standard receptacle and cap

### SL series Features



### SL60-240W



#### SL series items

Item No.	LAL-SL-240WL2	LAL-SL-200WL2	LAL-SL-150WL2	LAL-SL-100WL2	LAL-SL-75W	LAL-SL-60W
Power	240W	200W	150W	100W	75W	60W
Input Voltage	100-277V / 180-528VAC 50/60Hz					
Beam angle	T2/T3/T4					
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K					
Sensor	3 pins / 5 pins / 7 pins NEMA base / Photocell sensor					
Dim	1-10V / Dali dimmable ; LoraWan / Zigbee / Zhaga City Smart Control					
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90					
Materials	Die casting aluminum heat sink + Optical Lens + Tempered glass					
Light efficiency	150Lm/W; Tool Free Opening					
Spec.	Working temperature : -30° C --50° C / IP66 Waterproof / IK08/ 50,000Hrs Lifespan / 5 years warranty					

#### SL-series application

Street, road, pathway, parking lot, highway, high mast, public area etc.



L LED street light Series




ZHAGA standard extension receptacle and cap

NEMA standard receptacle and cap

SL series Features



**Tool-free operation, Easy Maintenance.**



SL30-240W



SL series items

Item No.	LAL-SL-240W	LAL-SL-200W	LAL-SL-150W	LAL-SL-120W	LAL-SL-100W	LAL-SL-75W	LAL-SL-60W	LAL-SL-50W/40W
Power	240W	200W	150W	120W	100W	75W	60W	50W/40W
Input Voltage	100-277V / 180-528VAC 50/60Hz							
Beam angle	T2/T3/T4							
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K							
Sensor	3 pins / 5 pins / 7 pins NEMA base / Photocell sensor							
Dim	1-10V / Dali dimmable ; LoraWan / Zigbee / Zhaga City Smart Control							
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90							
Materials	Die casting aluminum heat sink + Optical Lens + Tempered glass							
Light efficiency	140Lm/W							
Spec.	Working temperature : -30° C --50° C / IP66 Waterproof / IK08/ 50,000Hrs Lifespan / 5 years warranty							
Net Weight	11.5Kg	11.5Kg	7.2Kg	6.13Kg	6Kg	5.9Kg	3.3Kg	3.2Kg

SL-series application

Street, road, pathway, parking lot, highway, high mast, public area etc.



G LED street light Series



ZHAGA standard extension receptacle and cap      NEMA standard receptacle and cap

SL series Features



**Tool-free operation, Easy Maintenance.**



SL60-240W



SL series items

Item No.	LAL-SL-300WG	LAL-SL-204WG	LAL-SL-200WG	LAL-SL-150WG	LAL-SL-100WG	LAL-SL-75WG	LAL-SL-50WG
Power	300W	240W	200W	150W	100W	75W	50W
Input Voltage	100-277V / 180-528VAC 50/60Hz						
Beam angle	T2/T3/T4						
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K						
Sensor	3 pins / 5 pins / 7 pins NEMA base / Photocell sensor						
Dim	1-10V / Dali dimmable ; LoraWan / Zigbee / Zhaga City Smart Control						
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90						
Materials	Die casting aluminum heat sink + Optical Lens + Tempered glass						
Light efficiency	150Lm/W; Tool Free Opening						
Spec.	Working temperature : -30° C --50° C / IP66 Waterproof / IK08/ 50,000Hrs Lifespan / 5 years warranty						

SL-series application

Street, road, pathway, parking lot, highway, high mast, public area etc.



### E LED street light Series




ZHAGA standard extension receptacle and cap      NEMA standard receptacle and cap

### SL series Features



**Tool-free operation, Easy Maintenance.**



### SL60-240W



#### SL series items




Item No.	LAL-SL-200WE	LAL-SL-150WE	LAL-SL-120WE	LAL-SL-100WE	LAL-SL-75WE	LAL-SL-50WE
Power	200W	150W	120W	100W	75W	50W
Input Voltage	100-277V / 180-528VAC 50/60Hz					
Beam angle	T2/T3/T4					
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K					
Sensor	3 pins / 5 pins / 7 pins NEMA base / Photocell sensor					
Dim	1-10V / Dali dimmable ; LoraWan / Zigbee / Zhaga City Smart Control					
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90					
Materials	Die casting aluminum heat sink + Optical Lens + Tempered glass					
Light efficiency	150Lm/W; Tool Free Opening					
Spec.	Working temperature : -30° C --50° C / IP66 Waterproof / IK08/ 50,000Hrs Lifespan / 5 years warranty					

#### SL-series application

Street, road, pathway, parking lot, highway, high mast, public area etc.



S LED street light  
Series Light Distribution  
Curve



SL40-200WS2



SL series items


Item No.	LAL-SL-200WS2	LAL-SL-150WS2	LAL-SL-120WS2	LAL-SL-100WS2	LAL-SL-80WS2	LAL-SL-60WS2	LAL-SL-40WS2
Power	200W	150W	120W	100W	80W	60W	40W
Input Voltage	100-277V / 180-528VAC 50/60Hz						
Beam angle	T2 / T3 / T4 / 60° / 90° / 120						
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K						
Sensor	3 pins / 5 pins / 7 pins NEMA base / Photocell sensor						
Dim	1-10V / Dali dimmable ; LoraWan / Zigbee / Zhaga City Smart Control						
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90						
Materials	Die casting aluminum heat sink + Optical Lens + Tempered glass						
Light efficiency	150Lm/W; 170Lm/W						
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty						
Mounting	Φ60mm pole mounting						

SL-S series application


Street, road, pathway, parking lot, highway, high mast, public area etc.



N LED street light  
Series Light Distribution  
Curve



SL-N series Size:



SL30-240WN



SL series items




Item No.	LAL-SL-240WN	LAL-SL-200WN	LAL-SL-150WN	LAL-SL-120WN	LAL-SL-100WN	LAL-SL-70WN	LAL-SL-50WN	LAL-SL-30WN
Power	240W	200W	150W	120W	100W	70W	50W	30W
Input Voltage	100-277V / 180-528VAC 50/60Hz							
Beam angle	T2							
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K							
Sensor	3 pins / 5 pins / 7 pins NEMA base / Photocell sensor							
Dim	1-10V / Dali / PWM / dimmable by Zigbee / DMX control							
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD5050; Ra70/Ra80/Ra90							
Materials	Die casting aluminum heat sink + Optical Lens							
Light efficiency	170Lm/W							
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty							
Net Weight	2.7Kg	2.61Kg	2.21Kg	1.93Kg	1.89Kg	1.63Kg	1.54Kg	1.15Kg

SL-N series application

Street, road, pathway, parking lot, highway, high mast, public area etc.



L LED street light  
Series Light Distribution  
Curve



SL40-200WN2



SL series items


Item No.	LAL-SL-200WN2	LAL-SL-150WN2	LAL-SL-120WN2	LAL-SL-100WN2	LAL-SL-80WN2	LAL-SL-60WN2	LAL-SL-40WN2
Power	200W	150W	120W	100W	80W	60W	40W
Input Voltage	100-277V / 180-528VAC 50/60Hz						
Beam angle	T2 / T3 /						
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K						
Sensor	3 pins / 5 pins / 7 pins NEMA base / Photocell sensor						
Dim	1-10V / Dali dimmable ; LoraWan / Zigbee / Zhaga City Smart Control						
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90						
Materials	Die casting aluminum heat sink + Optical Lens						
Light efficiency	150lm/W						
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty						
Mounting	Φ60mm pole / wall bracket mounting						

SL-N series application

Street, road, pathway, parking lot, highway, high mast, public area etc.



LED street light Series  
Light Distribution Curve



SL-C series Features



SL30-200WC



SL series items


Item No.	LAL-SL-200WC	LAL-SL-150WC	LAL-SL-100WC	LAL-SL-80WC	LAL-SL-60WC	LAL-SL-50WC	LAL-SL-30WC
Power	200W	150W	100W	80W	60W	50W	30W
Input Voltage	110V/ 1605-265V 50/60Hz						
Beam angle	T1/T2/T3/T4/T5						
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K						
Dim	1-10V / Dali / PWM /pre-program dimmable						
Driver /LEDs	Meanwell / Sosen / Inventronics ; SMD2835; Ra70						
Materials	Die casting aluminum heat sink + Optics lens + Tempered Glass						
Light Efficiency	130Lm/W						
Spec.	Working temperature : -30° C --45° C / IP66 Waterproof / 50,000Hrs Lifespan / 3 years warranty						
Net Weight	3.13Kg	2.73Kg	2.73Kg	1.75Kg	1.75Kg	1.15Kg	1.15Kg

SL-series application

Street, road, pathway, parking lot, highway, high mast, public area etc.



### LED street light Series Light Distribution Curve




III

IV

V

### SLB-series Features

#### Photocell Sensor / Pre-program Time Sensor



### SLB70-300W



#### SLB series items


Item No.	LAL-SLB-01	LAL-SLB-01-2	LAL-SLB-02	LAL-SLB-03	LAL-SLB-04	LAL-SLB-05
Power	300W	240W	200W	150W	100W	70W
Input Voltage	100-277V / 180-528VAC 50/60Hz					
Beam angle	Type III/IV/V					
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K					
Sensor	Photocell sensor					
Dim	1-10V / Dali / PWM /pre-program dimmable					
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90					
Materials	Die casting aluminum heat sink + PC lens					
Light efficiency	130Lm/W					
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty					
Net Weight	13.06Kg	11.04Kg	8.51Kg	6.57Kg	5.52Kg	4.3Kg

#### SLB-series application


Street, road, pathway, parking lot, highway, high mast, public area etc.



L LED street light  
Series Light Distribution  
Curve



SL-L series Features



SL30-300WL



SL series items ▼


Item No.	LAL-SL-300WL3	LAL-SL-240WL3	LAL-SL-200WL3	LAL-SL-150WL3	LAL-SL-100WL3	LAL-SL-80WML3	LAL-SL-60WML3	LAL-SL-30WML3
Power	300W	240W	200W	150W	100W	80W	60W	30W
Input Voltage	100-277V / 180-528VAC 50/60Hz							
Beam angle	Type II / III							
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K							
Sensor	3 pins / 5 pins / 7 pins Photocell sensor;							
Dim	1-10V / Dali / PWM /pre-program dimmable							
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90							
Materials	Die casting aluminum heat sink + PC Lens + Tempered glass							
Light efficiency	150Lm/W							
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / IK08/ 50,000Hrs Lifespan / 5 years warranty							
Net Weight	7.9Kg	6.79Kg	6.79Kg	6.13Kg	5.2Kg	5.2Kg	4.3Kg	4.3Kg

SL-series application ▼

Street, road, pathway, parking lot, highway, high mast, public area etc.




LED street light Series  
Light Distribution Curve



80\*140°

SL-series Features



Slim design, easy installation

Die casting heat sink

High Performance Power Driver

SL50-300WL



SL series items

Item No.	LAL-SL-300WL1	LAL-SL-240WL1	LAL-SL-200WL1	LAL-SL-150WL1	LAL-SL-100WL1	LAL-SL-50WL1
Power	300W	240W	200W	150W	100W	50W
Input Voltage	100-277V / 180-528VAC 50/60Hz					
Beam angle	80*140°					
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K					
Dim	1-10V / Dali / PWM /pre-program dimmable					
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90					
Materials	Die casting aluminum heat sink					
Light efficiency	130Lm/W					
Spec.	Working temperature : -35° C--50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty					
Net Weight	6.35Kg	5.33Kg	4.79Kg	3.81Kg	3.43Kg	2.96Kg

SL-series application

Street, road, pathway, parking lot, highway, high mast, public area etc.



## PT30-150WM LED garden light



### PT-Mseries items

Item No.	LAL-PT-120WM	LAL-PT-100W/90WM	LAL-PT-75WM	LAL-PT-60WM	LAL-PT-50WM	LAL-PT-40WM
Power	120W	100W/90W	75W	60W	50W	40W
Input Voltage	100-277V / 180-528VAC 50/60Hz					
Beam angle	60° / 90° / T2 / T3 / T4					
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K					
Sensor	Photocell sensor; 3/5/7 pins NEMA Base; City Smart control options : Zigbee / LoRaWAN / Zhaga					
Dim	0-10V / Dali / PWM /pre-program dimmable					
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90					
Materials	Die casting aluminum heat sink + PC lens + Tempered glass					
Size	W500*H184mm					
Light efficiency	150Lm/W; Tool Free Opening					
Spec.	Working temperature : -30° C --50° C / IP66 Waterproof / IK08 / 50,000Hrs Lifespan / 5 years warranty					

### PT-series application

Garden, street, road, pathway, yard, parking lot, public area, landscape, decorative lighting etc.



## PT40-90WY LED garden light



### PT-Y series items

Item No.	LAL-PT-90WY	LAL-PT-75WY	LAL-PT-60WY	LAL-PT-50WY	LAL-PT-40WY
Power	90W	75W	60W	50W	40W
Input Voltage	100-277V / 180-528VAC 50/60Hz				
Beam angle	60° / 90° / T2 / T3 / T4				
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K				
Sensor	Photocell sensor; 3/5/7 pins NEMA Base; City Smart control options : Zigbee / LoRaWAN / Zhaga				
Dim	1-10V / Dali / PWM /pre-program dimmable				
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90				
Materials	Die casting aluminum heat sink + PC lens + Tempered glass				
Size	W460*H515mm				
Light efficiency	150Lm/W; ; Tool Free Opening				
Spec.	Working temperature : -30° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty				

### PT-series application

Garden, street, road, pathway, yard, parking lot, public area, landscape, decorative lighting etc.



## PT40-150WR LED garden light



PT-R series items ▼

Item No.	LAL-PT-150W/120WR	LAL-PT-100W/90WR	LAL-PT-75WR	LAL-PT-60WR	LAL-PT-50WR	LAL-PT-40WR
Power	150W/120W	100W/90W	75W	60W	50W	40W
Input Voltage	100-277V / 180-528VAC 50/60Hz					
Beam angle	60° / 90° / T2 / T3 / T4					
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K					
Sensor	Photocell sensor; 3/5/7 pins NEMA Base; City Smart control options : Zigbee / LoRaWAN / Zhaga					
Dim	0-10V / Dali / PWM /pre-program dimmable					
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90					
Materials	Die casting aluminum heat sink + PC lens + Tempered glass					
Size	W520*H230mm					
Light efficiency	170Lm/W; Tool Free Opening					
Spec.	Working temperature : -30° C --50° C / IP66 Waterproof / IK08 / 50,000Hrs Lifespan / 5 years warranty					

## PT-series application ▼

Garden, street, road, pathway, yard, parking lot, public area, landscape, decorative lighting etc.



## PT40-150WS LED garden light



PT-S series items ▼

Item No.	LAL-PT-150W/120WR	LAL-PT-100W/90WR	LAL-PT-75WR	LAL-PT-60WR	LAL-PT-50WR	LAL-PT-40WR
Power	150W/120W	100W/90W	75W	60W	50W	40W
Input Voltage	100-277V / 180-528VAC 50/60Hz					
Beam angle	60° / 90° / 120° / T2 / T3 / T4					
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K					
Sensor	Photocell sensor; 3/5/7 pins NEMA Base; City Smart control options : Zigbee / LoRaWAN / Zhaga					
Dim	0-10V / Dali / PWM /pre-program dimmable					
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90					
Materials	Die casting aluminum heat sink + PC lens + Tempered glass					
Size	W520*H230mm					
Light efficiency	150Lm/W					
Spec.	Working temperature : -30° C --50° C / IP66 Waterproof / IK08 / 50,000Hrs Lifespan / 5 years warranty					

## PT-series application ▼

Garden, street, road, pathway, yard, parking lot, public area, landscape, decorative lighting etc.



## PT30-150W LED garden light



PT-series items 

Item No.	LAL-PT-100WC	LAL-PT-80WC	LAL-PT-75WC	LAL-PT-60WC	LAL-PT-50WC	LAL-PT-40WC
Power	100W	90W	75W	60W	40W	60W
Input Voltage	100-277V / 180-528VAC 50/60Hz					
Beam angle	120° / T2 / T3 / T4					
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K					
Sensor	Photocell sensor					
Dim	1-10V / Dali / PWM /pre-program dimmable					
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90					
Materials	Die casting aluminum heat sink					
Size	591*276mm					
Light efficiency	150lm/W					
Spec.	Working temperature : -40° C --55° C / IP66 Waterproof / IK08 / 50,000Hrs Lifespan / 5 years warranty					

PT-series application 

Garden, street, road, pathway, yard, parking lot, public area, landscape, decorative lighting etc.



## PT40-150W LED garden light




PT series items 

Item No.	LAL-PT-150W3	LAL-PT-120W3	LAL-PT-100W3	LAL-PT-75W3	LAL-PT-60W3	LAL-PT-40W3
Power	150W	120W	100W	75W	60W	40W
Input Voltage	100-277V / 180-528VAC 50/60Hz					
Beam angle	120°					
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K					
Sensor	Photocell sensor					
Dim	1-10V / Dali / PWM /pre-program dimmable					
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90					
Materials	Die casting aluminum heat sink					
Size	600*377mm					
Light efficiency	130lm/W					
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty					

PT-series application 

Garden, street, road, pathway, yard, parking lot, public area, landscape, decorative lighting etc.



## PT40-150W LED garden light



PT series items ▼

Item No.	LAL-PT-150W	LAL-PT-120W	LAL-PT-100W	LAL-PT-90W	LAL-PT-75W	LAL-PT-60W	LAL-PT-50W	LAL-PT-40W
Power	150W	120W	100W	90W	75W	60W	50W	40W
Input Voltage	100-277V / 180-528VAC 50/60Hz							
Beam angle	90° / 120° / 80*145°							
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K							
Sensor	Photocell sensor							
Dim	1-10V / Dali / PWM /pre-program dimmable							
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90							
Materials	Die casting aluminum heat sink							
Size	450*450*524mm							
Light efficiency	130Lm/W							
Spec.	Working temperature : -40° C --55° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty							

### PT-series application ▼

Garden, street, road, pathway, yard, parking lot, public area, landscape, decorative lighting etc.



## PR40-150W LED garden light



PR series items ▼

Item No.	LAL-PR-150W	LAL-PR-120W	LAL-PR-100W	LAL-PR-90W	LAL-PR-75W	LAL-PR-60W	LAL-PR-50W	LAL-PR-40W
Power	150W	120W	100W	90W	75W	60W	50W	40W
Input Voltage	100-277V / 180-528VAC 50/60Hz							
Beam angle	150° / 80*145°							
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K							
Sensor	Photocell sensor							
Dim	1-10V / Dali / PWM /pre-program dimmable							
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90							
Materials	Die casting aluminum heat sink							
Size	441*357mm							
Light efficiency	130Lm/W							
Spec.	Working temperature : --35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty							

### PR-series application ▼

Garden, street, road, pathway, yard, parking lot, public area, landscape, decorative lighting etc.



## AL30-100W LED garden light



Black

Grey


Green

AL series items

Item No.	LAL-AL-120WD	LAL-AL-100WD	LAL-AL-75WD	LAL-AL-60WD	LAL-AL-50W/40WD
Power	120W	100W	75W	60W	50W/40W
Input Voltage	100-277V / 180-528VAC 50/60Hz				
Beam angle	60° / 90° / T2/T3/T4				
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K				
Sensor	Photocell sensor				
Dim	1-10V / Dali / PWM /pre-program dimmable				
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90				
Materials	Extruded aluminum heat sink				
Size	400*400*662mm				
Light efficiency	130Lm/W				
Spec.	Working temperature : -30° C --50° C / IP66 Waterproof / IK08/ 50,000Hrs Lifespan / 5 years warranty				

AL-series application

Garden, street, road, pathway, yard, parking lot, public area, landscape, decorative lighting etc.



## AL60-150W LED garden light




AL series items

Item No.	LAL-AL-150W	LAL-AL-120W	LAL-AL-100W	LAL-AL-90W	LAL-AL-75W	LAL-AL-60W
Power	150W	120W	100W	90W	75W	60W
Input Voltage	100-277V / 180-528VAC 50/60Hz					
Beam angle	150° / 80*145°					
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K					
Sensor	Photocell sensor					
Dim	1-10V / Dali / PWM /pre-program dimmable					
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90					
Materials	Die casting aluminum heat sink					
Size	360*360*504mm					
Light efficiency	130Lm/W					
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty					

AL-series application

Garden, street, road, pathway, yard, parking lot, public area, landscape, decorative lighting etc.



## Integrated Bifacial Solar LED Street Light Series

5050 LED chip

OSRAM PHILIPS

LiFePO4/Ternary lithium

CATL BYD

MPPT/PWM Controller

SRNE Depower

MPPT

4G

※Time control/Microwave/PIR/Complementary power supply/IoT

■ ■ Body color options

Magnalium frame

Metal bracket

ADC12 Die cast end cap, Battery box, Adapter handle

Double-sided monocrystal

PIR Microwave

0 100° 0 100°

0 10-30s 0 10-150s

0 10-30s 0 10-150s



- Feature:
- ★ Appearance patent
  - ★ Double-sided monocrystal, higher conversion efficiency
  - ★ Multiple types of optical lens for different road lighting
  - ★ Waterproof gold plated plug, high transmission efficiency
  - ★ Adjust adapter at a large angle, meet installation requirements, can choose rod installation pole sleeve and wall mounted pole sleeve
  - ★ Tool-free battery box, easy to maintain
  - ★ IP66 protection

## SSL-S



### SSL-S series items


Item No.	LAL-SSL-400WS	LAL-SSL-300WS	LAL-SSL-200WS	LAL-SSL-100WS
Power	40W	30W	24W	18W
Solar Panel	6V 60W	6V 50W	6V 40W	6V 30W
Lumens Efficiency	7200Lm	6000Lm	4800Lm	3000Lm
Battery LiFePO4	3.2V 90AH	3.2V 75AH	3.2V 60AH	3.2V 45AH
Charging Time	6-7 hours(by Sun)			
Working time	12 Hrs & 3-5 rain days			
Mounting height	8-10M	6-8M	6-8M	6-8M
Controller	12-Hour Intelligent Power Mode: Motion Detected: 100% brightness; No Motion Detected: 20% brightness; Lighting Duration After Motion Detected: 10 seconds			
Spec.	SMD5050 CCT: 3000K/4000K/5000K/6500K; Beam angle: 75°*150° IP66 waterproof / IK08/ 3 years warranty			

### SSL-S series application

Street, road, pathway, parking lot, highway, high mast, public area etc.



### Integrated Solar LED Street Light Series



### SSL-N 30W-150W



#### SSL-N series items


Item No.	LAL-SSL-150WN	LAL-SSL-120WN	LAL-SSL-100WN	LAL-SSL-60WN	LAL-SSL-50WN	LAL-SSL-40WN
Power	150W	120W	100W	60W	50W	40W
Solar Panel	36V 150W	36V 110W	36V 110W	18V 80W	18V 65W	18W 50W
Lumens Efficiency	180-200lm/W					
Battery LiFeP04	25.6V 768WH	25.6V 614WH	25.6V 460WH	12.8V 384WH	12.8V 230.4WH	3.2V 192WH
Charging Time	6-7 hours(by Sun)					
Working time	12 Hrs & 3-5 rain days					
Mounting height	10-12M	6-10M	6-10M	6-10M	6-8M	6-8M
Controller	Time control / Induction control / Time + induction control					
Spec.	SMD3030 CCT: 3000K/4000K/5000K/6500K; Beam angle: 75*150° . / IP66 waterproof / IK08/ 5 years warranty					

#### SSL-series application

Street, road, pathway, parking lot, highway, high mast, public area etc.



### Integrated Solar LED street light Series Light Distribution Curve



### SSL-H 30W-150W




#### SSL-H series items

Item No.	LAL-SSL-150W	LAL-SSL-120WH	LAL-SSL-100WH	LAL-SSL-80WH	LAL-SSL-60WH	LAL-SSL-40WH	LAL-SSL-30WH
Power	150W	120W	100W	80W	60W	40W	30W
Solar Panel	36V 150W	36V 120W	18V 75W	18V 60W	18V 50W	18V 35W	6V 25W
Lumens Efficiency	180-200Lm/W						
Battery	25.6V 28AH	25.6 22AH	12V 30AH	12V 20AH	12V 16AH	12V 12AH	3.2V 24AH
Charging Time	6-7 hours(by Sun)						
Working time	12 Hrs & 3-5 rain days						
Mounting height	10-12M	6-10M	6-10M	6-10M	6-8M	6-8M	4-6M
Controller	Time control / Induction control / Time + induction control						
CCT	3000K/4000K/5000K/6500K						

#### SSL-series application

Street, road, pathway, parking lot, highway, high mast, public area etc.





## SSL-12W-120W



### SSL series items

Item No.	LAL-SSL-120W	LAL-SSL-100W	LAL-SSL-80W	LAL-SSL-60W	LAL-SSL-50W	LAL-SSL-40W	LAL-SSL-30W	LAL-SSL-20W	LAL-SSL-15W
Power	120W	100W	80W	60W	50W	40W	30W	20W	15W
Solar Panel	30V 170W	30V 110W	30V 110V	18V 75W	18V 75W	18V 50W	18V 50W	18V 50W	18V 30W
Lumens Efficiency	180-200lm/W								
Battery	12V 66AH	12V 54AH	12V 48AH	12V 38AH	12V 31AH	12V 24AH	12V 20AH	12V 18AH	12V 12AH
Charging Time	6-7 hours(by Sun)								
Working time	12 Hrs & 3-5 rain days								
Mounting height	6-10M 6-10M	6-10M	6-8M	6-8M	6-8M	4-6M	4-6M	4-6M	4-6M
Controller	Time control / Induction control / Time + induction control								
CCT	3000K/4000K/5000K/6500K								

### SL-series application

Street, road, pathway, parking lot, highway, high mast, public area etc.



1 Press the on/off button to activate the fixture.



2 Fasten the screws to finish the installation on the pole.



3 When the light is above 10lux, it will turn off the light automatically, solar panel starts to charge.



4 When the light is under 10lux, it will turn on the light automatically, battery starts to work.





5 When people come near about 6 meters, it will change to 100% power for better brightness.



6 When people walk away about 6 seconds, it will change to 20% power for longer lighting time.

### Integrated Solar LED Flood Light Series



### SSL-F 20W-60W



#### SSL-F series items


Item No.	LAL-SSF-60W	LAL-SSF-50W	LAL-SSF-40W	LAL-SSF-30W	LAL-SSF-20W
Power	60W	50W	40W	30W	20W
Solar Panel	12.8V 80W	12.8V 60W	12.8V 50W	3.2V 40W	3.2V 30W
Lumens Efficiency	180Lm/W				
Battery LiFeP04	307.2WH	230.4WH	153.6WH	115.2WH	76.82WH
Charging Time	6-7 hours(by Sun)				
Working time	12 Hrs & 3-5 rain days				
Mounting height	6-10M	6-10M	6-10M	6-10M	6-8M
Controller	Time control / Induction control / Time + induction control				
Spec.	SMD3030 CCT: 3000K/4000K/5000K/6500K; Beam angle: 90° / 120° / T2 / P60 / IP66 waterproof / IK08/ 5 years warranty				

#### SSL-F series application

Street, road, pathway, parking lot, highway, high mast, public area, billboard,, garden, park, etc.



Panel LED high bay light Series  
Light Distribution Curve



Die casting Aluminum housing



Tempered glass ( Frosted PC cover options)

30°/60°/90° /120°/ 30\*120°/ 90\*120°



SHB100-300WE



SHB series items


Item No.	LAL-SHB-300WE	LAL-SHB-240WE	LAL-SHB-200WE	LAL-SHB-150WE	LAL-SHB-100WE
Power	300W	240W	200W	150W	100W
Input Voltage	100-277V / 180-528VAC 50/60Hz				
Size	585*270*54mm	460*270*54mm	460*270*54mm	360*260*54mm	360*260*54mm
Beam angle	30° /60° /90° /120° / P50 / Frosted tempered glass				
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K				
Dim	0-10V / Dali 2 / PWM dimmable by DALI/Zigbee /DMX / Tuya Smart control				
Sensor	Motion / Daylight Sensor				
Driver /LEDs	Meanwell /Philips / Sosen / Lifud / Inventronics driver ; SM3030 ; Ra70/Ra80/Ra90				
Materials	Die casting aluminum heat sink + Optical lens + Tempered glass				
Light efficiency	140Lm/W ; 160Lm/W				
Spec.	Working temperature : -30° C --45° C / IP66 / IK08 / UGR<19 / <25; 50,000Hrs Lifespan / 5 years warranty				

SHB-series application

Indoor sport field courts, warehouse, factory, workshop, store, supermarket, office, meeting room, showroom, etc.



## UFO LED high bay light Series Light Distribution Curve



## UHB-series Features & Accessories:

**Plug & Play Sensor**

Integrated motion sensor can be programmed to increase energy-saving, customized detection range, daylight, threshold, timer, and dimming settings.

**Excellent Heat Dissipation**

The well-proportioned ribs lay the foundation for the high-quality heat dissipation of the product.

**Anti-Glare Reflector**

Use this reflector to reduce glare from your 100-200-Watt UFO LED High-Bay Light and to create a traditional high-bay look. The reflector installs around the fixture's lens and comes with 4 screws to secure it in place.

Micro-wave Induction

Infrared Induction

Tuya Induction

Philips LED Driver	Sosen LED Driver	Lifud LED Driver	Alum Reflector (Standard)	Alum Reflector (Tall)	PC Reflector	Safe Guard
60°/90° PC Lenses	120° PC Lenses	UGR<19 PC Lenses	120° Tempered Glass	Adjustable Bracket	Safety Chain	Motion Sensor

## UHB100-240WN



### UHB series items


Item No.	LAL-UHB-01N	LAL-UHB-02N	LAL-UHB-03N	LAL-UHB-04N	LAL-UHB-05N
Power	240W	200W	150W	100W	60W
Input Voltage	100-277V / 180-528VAC 50/60Hz				
Size	Φ350*178mm	Φ310*178mm	Φ270*167mm	Φ230*157mm	Φ230*157mm
Beam angle	60° / 90° / 120°				
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K				
Dim	1-10V / Dali 2 / PWM dimmable by DALI/Zigbee / DMX / Tuya Smart control				
Sensor	Motion / Daylight Sensor				
Driver /LEDs	Philips / Sosen / Lifud driver ; SMD2835 ; Ra70/Ra80/Ra90				
Materials	Die casting aluminum heat sink + Optical lens; Clear PC /Aluminum reflector				
Light efficiency	150LM/W ; 170Lm/W; 190Lm/W;				
Spec.	Working temperature : -30° C --45° C / IP65 / IK09 / UGR<19 / <25; 50,000Hrs Lifespan / 5 years warranty				
Net Weight	3.0Kg	2.5Kg	1.8Kg	1.4Kg	1.4Kg

### UHB-series application

Indoor sport field courts, warehouse, factory, workshop, store, supermarket, office, meeting room, showroom, etc.



UFO LED high bay light  
Series Light Distribution  
Curve



UHB-series Features

**Extreme Efficacy 210lm/W**  
Up to 300W

300W  
1000W HID METAL HALIDE LAMP

210lm/W

300W High Ceiling Lighting Fixture  
Fully Replace 1000W HID / Metal Halide Lamp

**Remote-Controlled UFO Light**

Step into smart lighting with our intelligent UFO High Bay Light. Whether microwave or infrared sensor, your choice. Adjust brightness, color, and timers seamlessly through the remote control. Illuminate instantly with sensor control. Manage groups of lights effortlessly.

**Sensor System**

Integrated motion sensor can be programmed to increase energy-saving, customized detection range, daylight, threshold, timer, and dimming settings.

Microwave Induction  
Infrared Induction

**Efficient in Energy and Light**

Under similar lighting conditions, our high light efficiency LED consumes less power, delivering substantial energy savings. This underscores its remarkable efficiency in both light output and energy conservation!

100W - 210lm/w  
210W - 100lm/w

**Anti-Glare Reflector**

Use this reflector to reduce glare from your 100-150-200-Watt UFO LED High-Bay Light and to create a traditional High-bay look. The reflector installs around the fixture's lens and comes with 4 screws to secure it in place.

**Power & CCT adjustable**

100W 150W 200W

ON 1 2 ON 1 2 ON 1 2

60% 80% 100%

4000K 5000K 5700K

UHB100-300W



UHB series items


Item No.	LAL-UHB-01A	LAL-UHB-01	LAL-UHB-02	LAL-UHB-03	LAL-UHB-04
Power	300W	240W	200W	150W	100W
Input Voltage	100-277V / 180-528VAC 50/60Hz				
Size	Φ400*143mm	Φ400*134mm	Φ349*178mm	Φ309*178mm	Φ273*173mm
Beam angle	60° / 90° / 120°				
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K				
Dim	1-10V / Dali / PWM dimmable by DALI/Zigbee /DMX / Tuya Smart control / CCT & Power selected				
Sensor	Motion / Daylight Sensor				
Driver /LEDs	Philips / Sosen / Lifud driver ; SMD2835 ; Ra70/Ra80/Ra90				
Materials	Die casting aluminum heat sink + Optical lens; Clear PC /Aluminum reflector				
Light efficiency	150LM/W ; 170Lm/W; 190Lm/W; 210Lm/W				
Spec.	Working temperature : -30° C --45° C / IP65 / IK09 / UGR<19 / <25; 50,000Hrs Lifespan / 5 years warranty				
Net Weight	3.98Kg	3.53Kg	2.8Kg	2.3Kg	1.9Kg

UHB-series application


Indoor sport field courts, warehouse, factory, workshop, store, supermarket, office, meeting room, showroom, etc.



Food Factory Grade LED high bay light  
Series Light Distribution Curve



Dip switch: Power selectable



**UHB100-200W**



UHB series items ▼


Item No.	LAL-UHB-02X	LAL-UHB-03X	LAL-UHB-04X
Power	200W-150W-100W	150W-120W-100W	100W-80W-60W
Input Voltage	100-277VAC 50/60Hz		
Size	Φ345*143mm	Φ300*125mm	Φ300*125mm
Beam angle	60° / 90° / 120°		
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K		
Dim	1-10V /PWM ; Power selectable		
Sensor	Motion / Daylight Sensor		
Driver /LEDs	Lifud driver ; SMD2835 ; Ra70/Ra80/Ra90		
Materials	Die casting aluminum heat sink + Optical lens; Clear PC /Aluminum reflector		
Light efficiency	150LM/W		
Spec.	Working temperature : -30° C --45° C / IP65 / IK09 / UGR<19 / <25; 50,000Hrs Lifespan / 5 years warranty		
Net Weight	2.6Kg	1.7Kg	1.7Kg

UHB-series application ▼


Indoor sport field courts, warehouse, factory, workshop, store, supermarket, office, meeting room, showroom, etc.



### LED High Temperature Light Series Light Distribution Curve



### UHB-series Features



### UHB100-200W



### UHB series items


Item No.	LAL-UHB-02G2	LAL-UHB-03G2	LAL-UHB-04G2
Power	200W	150W	100W
Input Voltage	200-240VAC 50/60Hz		
Size	Φ400*455mm	Φ350*376mm	Φ310*368mm
Beam angle	60° / 90° / 120°		
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K		
Dim	1-10V / Dali / PWM dimmable		
Sensor	Microwave / daylight exterior or interiro Sensor		
Driver /LEDs	Philips / Sosen driver ; Epistar SMD2835 ; Ra70/Ra80/Ra90		
Materials	Die casting aluminum heat sink		
Light efficiency	150LM/W ; 170Lm/W		
Spec.	Working temperature : -30° C -- 70° C / IP66 Waterproof / 50,000Hrs Lifespan / 3 years warranty		
Net Weight	4.32Kg	2.8Kg	2.3Kg

### UHB-series application

High temperature area: steel, paper, glass, heat treatment metal forging workshop etc...



UFO LED high bay light  
Series Light Distribution  
Curve



UHB-series Features

High Power LED High Bay  
Up to 500W

500W  
1500W HID / METAL HALIDE LAMP



Narrow Angle

We provide lenses for common lighting angles such as 60°, 90°, and 120°, along with super-focused beams at 15°, 30° and 45° specially designed for high-voltage scenarios, delivering pinpoint illumination.



Anti-Glare Reflector

Use this reflector to reduce glare from your 100-150-200-Watt UFO LED High-Bay Light and to create a traditional high-bay look. The reflector installs around the fixture's lens and comes with 4 screws to secure it in place.



**Tailored Square Power Solutions:**  
Enhance your lighting experience by opting for square power supply solutions that suit your installation.

**Advanced Dali 2 Integration:**  
Unlock the potential of your lighting setup with the power of Dali 2 technology.

High Bay with Microwave Sensors



**Microwave Sensors :**  
Sensor direction: 180°  
Sensor coverage: Φ15M  
Installation height : 6-12M



Twist-on sensor module tool free, plug and play. one model for sensor or no



UHB100-500W



UHB series items


Item No.	LAL-UHB-500WG2	LAL-UHB-300WG2	LAL-UHB-01G2	LAL-UHB-02G2	LAL-UHB-03G2	LAL-UHB-04G2
Power	500W	300W	240W	200W	150W	100W
Input Voltage	100-277V / 180-528VAC 50/60Hz					
Size	Φ490*171mm	Φ400*147mm	Φ400*140mm	Φ350*171mm	Φ310*161mm	Φ260*156mm
Beam angle	60° / 90° / 120°					
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K					
Dim	1-10V / Dali / PWM dimmable					
Sensor	Microwave / daylight exterior or interiro Sensor					
Driver /LEDs	Philips / Sosen driver ; Epistar SMD2835 ; Ra70/Ra80/Ra90					
Materials	Die casting aluminum heat sink					
Light efficiency	150LM/W ; 170Lm/W; 190Lm/W; 210Lm/W					
Spec.	Working temperature : -30° C --45° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty					
Net Weight	4.32Kg	3.98Kg	3.53Kg	2.8Kg	2.3Kg	1.9Kg

UHB-series application

Indoor sport field courts, warehouse, factory, workshop, store, supermarket, office, meeting room, showroom, etc.



LED high bay light with reflector  
Series Light Distribution Curve



HB-series Features



- AL 1070 Fin aluminum housing for better heat dissipation, surface oxidation with matt black, anti-corrosion.
- With Lumileds SMD3030 LEDs, Ra80 high CRI.
- World famous high quality driver brand: Meanwell, Inventronics, Sosen etc. .
- Various beam angles optional for different applications.
- Up to 50,000 hours lifespan.
- Easy to install and maintain.

HB50-200W




HB series items


Item No.	LAL-HB515-200W	LAL-HB515-150W	LAL-HB515-100W	LAL-HB515-80W	LAL-HB515-50W
Power	200W	150W	100W	80W	50W
Input Voltage	100-277V / 180-528VAC 50/60Hz				
Beam angle	60° / 90° / 120°				
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K				
Dim	1-10V / Dali 2 dimmable				
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90				
Materials	Fin aluminum heat sink				
Light efficiency	130Lm/W				
Spec.	Working temperature : -30° C --45° C / IP66 / IK08 f / 50,000Hrs Lifespan / 5 years warranty				
Net Weight	4.2Kg	3.5Kg	2.68Kg	2.51Kg	1.56Kg

HB-series application


Indoor sport field courts, warehouse, factory, workshop, store, supermarket, office, meeting room, showroom etc.



## Linear LED high bay light Series Light Distribution Curve



## SHB-series Features



3D professional heat dissipation structure, inside and outside interlinked wind tunnel design, greatly improved thermal performance. Extend lifespan of the whole lamp



Adopt with high lumen Refond SMD3030 LEDs, CRI>80; 30° / 60° / 90° / 60 x 120° beam angle for different lighting solutions



Use world famous driver brand: Meanwell and Sosen. High performance



adjustable  $\pm 50^\circ$



Hanging chain



Side bracket

## SHB50-500W




## SHB series items


Item No.	LAL-SHB-500W	LAL-SHB-400W	LAL-SHB-300W	LAL-SHB-240W	LAL-SHB-200W	LAL-SHB-150W	LAL-SHB-100W	LAL-SHB-50W
Power	500W	400W	300W	240W	200W	150W	100W	50W
Input Voltage	100-277V / 180-528VAC 50/60Hz							
Beam angle	30° / 60° / 90° / 60*90° / 60*120°							
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K							
Dim	1-10V / Dali / PWM dimmable							
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90							
Materials	Extruded aluminum heat sink							
Light efficiency	140Lm/W							
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty							
Net Weight	13.06Kg	11.04Kg	8.51Kg	6.57Kg	5.52Kg	4.3Kg	3.18Kg	2.08Kg

## SHB-series application

Indoor sport field courts, warehouse, factory, workshop, store, supermarket, office, meeting room, showroom, plant growing etc.



Linear LED high bay light  
Series Light Distribution Curve



30°

60°

90°

60\*120°



**SHB50-240WC**




SHB series items


Item No.	LAL-SHB-240WC	LAL-SHB-200WC	LAL-SHB-180WC	LAL-SHB-150WC	LAL-SHB-120WC	LAL-SHB-100WC	LAL-SHB-50WC
Power	240W	200W	180W	150W	120W	100W	50W
Input Voltage	100-277V / 180-528VAC 50/60Hz						
Beam angle	30° / 60° / 90° / 60*90° / 60*120°						
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K						
Dim	0-10V / Dali / PWM dimmable						
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90						
Materials	Extruded aluminum heat sink + Optic lens						
Light efficiency	160lm/W						
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty						
Net Weight	4.67Kg	4.67Kg	3.41Kg	3.33Kg	2.25Kg	2.25Kg	1.37Kg

SHB-series application

Indoor sport field courts, warehouse, factory, workshop, store, supermarket, office, meeting room, showroom, plant growing etc.



### IK69K LED Tri-Proof Series Light Distribution Curve




### ST-E series features



#### 1 Standard




#### 2 DALI & 0/1-10V Dimmable




- Used for cable :0.75-1.5mm<sup>2</sup>
- Solid cable-end
- Wire stripping 10-12mm

#### Available Dimming Methods

Suggested Compatible Dimmers for DALI:  
 Tridonic | European market |  
 Lutron & Leviton | American market |  
 Philips Dynalite & Clipsal | Australian market |



\* Standard parts



\* Suspended accessories need to be paid additionally

### TP20-60W



### ST-series items


Item No.	LAL-TP-60W-150WS	LAL-TP-50W-150S	LAL-TP-50W-120S	LAL-TP-30W-60S
Power	60W	50W	50W	30W
Input Voltage	100-277V / 180-528VAC 50/60Hz			
LEDs	SMD2835			
CCT	3000K / 4000K / 5000K / 6500K			
Dim	1-10V / Dali / PWM dimmable			
Sensor	Microwave sensor / Emergency function options			
Beam angle	120°			
Size	W75*L1500mm	W75*L1500mm	W75*L1200mm	W75*L600mm
Light efficiency	130-150lm/W			
Spec.	Working temperature : -20° C --40° C / IP69K/ 50,000Hrs Lifespan / 5 years warranty			
Net Weight	2.41Kg	2.41Kg	1.91Kg	1.25Kg

### ST-E series application

Parking place / Car wash / Food & Meat factory / Chicken sheds / Livestock / Farms / Station / Offices / showroom etc.




LED Canopy Light Series Light Distribution Curve



120°

GS-A series Installations



GS100-240WA



GS series items


Item No.	LAL-GS-01A1	LAL-GS-01A2	LAL-GS-01A3	LAL-GS-01A4
Power	240W	200W	150W	100W
Input Voltage	100-277V / 180-528VAC 50/60Hz			
Beam angle	120°			
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K			
Dim	1-10V / Dali / PWM / pre-program dimmable			
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90			
Materials	Die casting aluminum heat sink			
Light efficiency	130Lm/W			
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty			
Net Weight	5.7Kg	5.7Kg	4.21Kg	4.21Kg

GS-A series application

Gas station, warehouse, canopy, corridor etc.



LED street light Series  
Light Distribution Curve




60°

90°

120°

GS-series Features



Lumileds SMD3030 LEDs, Ra80, LM80 standard, high efficiency; Long life span



**The Power Supply**

Adopt with High performance Meanwell driver




**Heat Dissipation**

Hollow design, perfect air convection, heat dissipation




**The Shell**

Module design, professional optical light distribution design together with modules, easy to disassemble, small size



Surface Ceiling Mounting



Recessed Mounting

GS80-200W



GS series items

Item No.	LAL-GS-200W	LAL-GS-150W	LAL-GS-120W	LAL-GS-80W	LAL-GS-60W
Power	200W	150W	120W	80W	60W
Input Voltage	100-277V / 180-528VAC 50/60Hz				
Beam angle	60° / 90° / 120°				
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K				
Dim	1-10V / Dali / PWM /pre-program dimmable				
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90				
Materials	Extruded aluminum heat sink				
Light efficiency	130Lm/W				
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty				
Net Weight	6.61Kg	6.53Kg	6.42Kg	3.9Kg	3.98Kg

GS-series application

Gas station, warehouse, canopy, corridor etc.



LED canopy light Series




GS-series Installations


Recessed mounting



Surface ceiling mounting



America ceiling mounting



GS60-150W



GS series items


Item No.	LAL-GS-01	LAL-GS-02	LAL-GS-03	LAL-GS-04	LAL-GS-05
Power	150W	120W	100W	80W	60W
Input Voltage	100-277V / 180-528VAC 50/60Hz 120°				
Beam angle	2700K/3000K / 4000K / 5000K/ 5700K / 6500K				
CCT	1-10V / Dali / PWM /pre-program dimmable				
Dim					
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90				
Materials	Die casting aluminum heat sink				
Light efficiency	130Lm/W				
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty				
Net Weight	6.61Kg	6.53Kg	6.42Kg	3.9Kg	3.98Kg

GS-series application

Gas station, warehouse, canopy, corridor etc.




LED street light Series  
Light Distribution Curve




120°

GS-series Installations

Ceiling mount with J-box



Pendent with 3/4 inch Conduit



GS45-120W



GS series items


Item No.	LAL-GS-02X	LAL-GS-03X	LAL-GS-04X	LAL-GS-05X	LAL-GS-06X
Power	120W	100W	75W	60W	45W
Input Voltage	100-277V / 180-528VAC 50/60Hz				
Beam angle	120°				
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K				
Dim	1-10V / Dali / PWM /pre-program dimmable				
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90				
Materials	Die casting aluminum heat sink				
Light efficiency	130Lm/W				
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty				
Net Weight	5.05Kg	4.97Kg	2.6Kg	2.53Kg	2.47Kg

GS-series application

Gas station, warehouse, canopy, corridor etc.




LED Canopy Light Series Light Distribution Curve




120°

GS-series Installations

Surface ceiling mounting



Pendent with 3/4 inch Conduit



GS100-150W



GS series items


Item No.	LAL-GS-01A	LAL-GS-02A	LAL-GS-03A
Power	150W	120W	100W
Input Voltage	100-277V / 180-528VAC 50/60Hz		
Beam angle	120°		
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K		
Dim	1-10V / Dali / PWM /pre-program dimmable		
Sensor	Motion Sensor		
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030; Ra70/Ra80/Ra90		
Materials	Die casting aluminum heat sink		
Light efficiency	130Lm/W		
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 5 years warranty		
Net Weight	5.75Kg	5.75Kg	5.63Kg

GS-series application


Gas station, warehouse, canopy, corridor etc.




ATEX Explosion Proof LED Flood Light Series Light Distribution Curve




Installations



1. Ceiling Type



2. Sitting Type



3. Suction Type

EXF 50W – 400W




EXF series items

Item No.	LAL-EXF-400W	LAL-EXF-300W	LAL-EXF-240W	LAL-EXF-200W	LAL-EXF-150W	LAL-EXF-100W	LAL-EXF-50W
Power	400W	300W	240W	200W	150W	100W	50W
Input Voltage	100-277V / 180-528VAC 50/60Hz						
Beam angle	60° / 90°						
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K						
Dim	1-10V / Dali / PWM dimmable						
Light Efficiency	130Lm/W						
Driver / LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD5050; Ra70/Ra80/Ra90						
Materials	Die casting aluminum heat sink + Tempered glass						
ATEX certified	Explosive-proof grade: II 2 G Ex db IIC T6 Gb; II 2 D Ex tb IIIC T80° C Db IP66						
Spec.	Working temperature : -25° C --50° C / IP66 Waterproof / IK08. / 50,000Hrs Lifespan / 5 years warranty						


EXF series applications



### ATEX Explosion Proof LED Industrial Light Series Light Distribution Curve



### Installations



### EXH 50W – 200W




### EXH series items

Item No.	LAL-EXH-280W	LAL-EXH-240W	LAL-EXH-200W	LAL-EXH-150W	LAL-EXH-100W	LAL-EXH-50W
Power	280W	240W	200W	150W	100W	50W
Input Voltage	100-277V / 180-528VAC 50/60Hz					
Beam angle	90° / 120°					
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K					
Dim	1-10V / Dali / PWM dimmable					
Light Efficiency	130Lm/W					
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD5050; Ra70/Ra80/Ra90					
Materials	Die casting aluminum heat sink + Tempered glass					
ATEX certified	Explosive-proof grade: Ex db IIC T6 Gb ; Ex tb III C T80°C Db					
Spec.	Working temperature : -25° C--50° C / IP66 Waterproof / IK08. / 50,000Hrs Lifespan / 5 years warranty					


### EXH series applications



### ATEX Explosion Proof LED Street Light Series Light Distribution Curve



### Installations



### EXS 50W – 200W



### EXS series items

Item No.	LAL-EXS-200W	LAL-EXS-150W	LAL-EXS-100W	LAL-EXS-50W
Power	200W	150W	100W	50W
Input Voltage	100-277V / 180-528VAC 50/60Hz			
Beam angle	90° / 120°			
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K			
Dim	1-10V / Dali / PWM dimmable			
Light Efficiency	130Lm/W			
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD5050; Ra70/Ra80/Ra90			
Materials	Die casting aluminum heat sink + Tempered glass			
ATEX certified	Explosive-proof grade: II 2 G Ex db IIC T6 Gb; II 2 G Ex db IIB T6 Gb; II 2 D Ex tb IIIC T80° C Db IP66			
Spec.	Working temperature : -25° C ~50° C / IP66 Waterproof / IK08. / 50,000Hrs Lifespan / 5 years warranty			

### EXS series applications





**Features**

Full aluminum heat sink; Environment temperature:-25° C~+45° C;  
1% light degradation at 2000hrs  
Full range input voltage:120V/ 220V/230V/240V/277VAC 50/60Hz;  
With SMD2835 LEDs, Ra80;  
GX24D GX24Q E27 E26 base options  
Frosted & clear cover option;  
NO UV and IR radiation, high quality, 3 years warranty.

360° series items

Item No.	LAL-360PLC-24WL	LAL-360PLC-21WL	LAL-360PLC-18WL	LAL-360PLC-15WL	LAL-360PLC-12WL	LAL-360PLC-9WL	LAL-360PLC-7WL	LAL-360PLC-5WL
Power	24W	21W	18W	15W	12W	9W	7W	5W
Size(mm)	Φ48* L204	Φ48* L188	Φ48* L172	Φ48* L156	Φ48* L132	Φ48* L116	Φ48* L108	Φ48* L108
Input Voltage	100-277V 50/60Hz							
Beam angle	360°							
CCT	3000K / 4000K / 6500K							
Base	GX24D/GX24Q/E27/E26							
Dim	Dim options							
Cover	Clear / Frosted glass							
Housing	Extruded aluminum heat sink							
Light efficiency	100Lm/W							
Spec.	Working temperature : -25° C --45° C / RA80/ 50,000Hrs Lifespan / 3 years warranty							



**LED Plug light**



**Features**

Full aluminum heat sink; Environment temperature:-25° C~+45° C;  
1% light degradation at 2000hrs  
Full range input voltage:120V/ 220V/230V/240V/277VAC 50/60Hz;  
With SMD2835 LEDs, Ra80;  
Different base options  
Milky & clear cover option;  
NO UV and IR radiation, high quality, 3 years warranty.

PLC series items

Item No.	LAL-PLA-11W-A	LAL-PLA-9W-A	LAL-PLA-7W-A	LAL-PLA-5W-A
Power	11W	9W	7W	5W
Size(mm)	Φ34* L172	Φ34* L158	Φ34* L144	Φ34* L120
Input Voltage	100-277V 50/60Hz			
Beam angle	120°			
CCT	3000K / 4000K / 6500K			
Base	G24D,G24Q, G23-2, Gx23-2, E27,E26,B22			
Dim	Dim options			
Cover	Clear / milky PC cover			
Housing	Extruded aluminum heat sink			
Light efficiency	100Lm/W			
Spec.	Working temperature : -30° C --45° C / RA80/ 50,000Hrs Lifespan / 3 years warranty			




## LED Energy Saving lamp



### Features

- Full aluminum heat sink; Environment temperature:-25° C~+45° C;
- 1% light degradation at 2000hrs
- Full range input voltage:120V/ 220V/230V/240V/277VAC 50/60Hz;
- Adopt with SMD2835 LEDs, Ra80;
- Different base options
- Frosted & clear cover option;
- NO UV and IR radiation, high quality, 3 years warranty.



### PLS series items

Item No.	LAL-PLC-8W	LAL-PLC-7W	LAL-PLC-6W	LAL-PLC-5W	LAL-PLC-4W	LAL-PLC-3W
Power	8W	7W	6W	5W	4W	3W
Size(mm)	Φ31* L234	Φ31* L180	Φ31*L180	Φ31*165	Φ31*135	Φ31*107
Input Voltage	100-277V 50/60Hz					
Beam angle	120°					
CCT	3000K / 4000K / 6500K					
Base	G23/GX23/2G7/2GX7					
Dim	Dim options					
Cover	Clear / Milky PC cover					
Housing	Extruded aluminum heat sink					
Light efficiency	100Lm/W					
Spec.	Working temperature : -25° C --45° C / RA80/ 50,000Hrs Lifespan / 3 years warranty					

## LED PL lamp



### Features


- Full aluminum heat sink; Environment temperature:-25° C~+45° C;
- 1% light degradation at 2000hrs
- Full range input voltage:120V/ 220V/230V/240V/277VAC 50/60Hz;
- With SMD2835 LEDs, Ra80;
- Frosted & clear cover option;
- NO UV and IR radiation, high quality, 3 years warranty.

### PLL series items


Item No.	LAL-PLL-22WA	LAL-PLL-22W	LAL-PLL-18W	LAL-PLL-12W	LAL-PLL-9W
Power	22W	22W	18W	12W	9W
Size(mm)	Φ38* L571	Φ38* L542	Φ38* L417	Φ38* L322	Φ38* L227
Input Voltage	100-277V 50/60Hz				
Beam angle	120°				
CCT	3000K / 4000K / 6500K				
Base	2G11				
Dim	Dim options				
Cover	Clear / Milky PC cover				
Housing	Extruded aluminum heat sink				
Light efficiency	100Lm/W				
Spec.	Working temperature : -30° C --45° C / RA80/ 50,000Hrs Lifespan / 3 years warranty				



LED Down Light Series  
Light Distribution  
Curve



CL series dimensions



50W

100W

150W



CL50-150W



ST-series items ▼

Item No.	LAL-CL-150W	LAL-CL-100W	LAL-CL-50W
Power	150W	100W	50W
Input Voltage	100-277V / 180-528VAC 50/60Hz		
LEDs	COB		
CCT	3000K / 4000K / 5000K / 6500K		
Dim	1-10V / Dali / PWM dimmable		
Materials	Fin aluminum housing + tempered glass		
Beam angle	25° / 45° / 60°		
Size	W235*H265mm	W225*H240mm	W170*H215mm
Light efficiency	130-150lm/W		
Spec.	Working temperature : -20° C --40° C / IP54/ 50,000Hrs Lifespan / 5 years warranty		

CL series application ▼

Shop, supermarket, home, office, hotel...




Linear LED Grow Light(Full Spectrum)


Sunlike White LEDs Full spectrum

**SunLike**  
Characteristics Graph


Fig 1. Color Spectrum, T<sub>j</sub> = 25°C




Golon RGB LEDs Full spectrum




Dimension: (mm)




50W



100W



150W



200W

SHB50-500W



SHB series items

Item No.	LAL-SHB-500W	LAL-SHB-400W	LAL-SHB-300W	LAL-SHB-240W	LAL-SHB-200W	LAL-SHB-150W	LAL-SHB-100W	LAL-SHB-50W
Power	500W	400W	300W	240W	200W	150W	100W	50W
Input Voltage	100-277V 50/60Hz							
Beam angle	30° / 60° / 90° / 60 x 120° / 30 x 70° / 80*155°							
CCT	Full Spectrum for plant grow							
Dim	1-10V / Dali / PWM dimmable options							
Materials	Extruded aluminum heat sink+ PC Lens							
Spec.	Working temperature : -35° C --50° C / IP66 Waterproof / 50,000Hrs Lifespan / 3 years warranty							
Net Weight	13.06Kg	11.04Kg	8.51Kg	6.57Kg	5.52Kg	4.3Kg	3.18Kg	2.08Kg


SHB-series application




Wall / Ceiling bracket

Hanging mounting

LED grow light ( Full Spectrum)




Control Function / Dimming options



120° Foldable

Dimension: (mm)




GW600-1200W




GW series items

Item No.	LAL-GW-600W	LAL-GW-750W	LAL-GW-1000W	LAL-GW-1200W
Power	600W	750W	1000W	1200W
Input Voltage	100-277V 50/60Hz			
Spectrum	Full Spectrum			
Beam angle	120° 2.7 μ			
PPE	mol/J.			
PPF	1620 μmol/S	2025 μmol/S	2700 μmol/S	3240 μmol/S
Dim	0-10V dimming			
IP grade	IP66 Waterproof			
Working temperature	-40° C --55° C			
Size	1120*1120*35mm	1120*1120*35mm	1120*1120*35mm	1450*1120*35mm
Spec.	CE approval, 3 years wararnty			


SHB-series Installation



- Step 1: Take out the whole light and hanging rope (2pcs). (Fig. 1)
- Step 2: Open and keep it on a clean surface, use (D) to make both sides basically straight and then fastened the clasp. (Fig. 2)
- Step 3: Replace the electronic box in the middle, fasten the bolt.
- Step 4: Fasten hanging rope E to the holes at the both sides of light, and fix installation end to the load-bearing body, then adjust installation height through F. (Fig. 3)



FL- Spotlight Series  
Light Distribution Curve



FL-series features

High power CREE LEDs with single lens & reflector, min 5° beam angle



360° Three-Dimension Heat dissipation Optimized thermal solution

Aesthetic Heatsink Module with dimensional Design

Maximum Contact between heatpipe and Fin Maximu heat dissipation

Ventilation vents under the heatsink provide enough air intake for cooling

The heat is discharged through the designed 360° air duct, with effective loop of air circulation and heat dissipation

FL400-1500WT



FL-series items


Item No.	LAL-FL-1500W	LAL-FL-1200W	LAL-FL-1000W	LAL-FL-800W	LAL-FL-600W	LAL-FL-500W	LAL-FL-400W-2
Power	1500W	1200W	1000W	800W	600W	500W	400W
Input Voltage	100-277V / 180-528VAC 50/60Hz						
Beam angle	5° / 8° / 10° / 15° / 30° / 60°						
CCT	2700K/3000K / 4000K / 5000K/ 5700K / 6500K / RGB by DMX control						
Dim	1-10V / Dali / PWM dimmable						
Surge Protection	SPD 20KV/10KV/6KV/4KV						
Driver /LEDs	Meanwell / Sosen / Inventronics ; CREE/Citizen COB LEDs ; Ra70/Ra80/Ra90						
Materials	Fin aluminum heat sink + built in copper pipe						
Light efficiency	120-130Lm/W						
Spec.	Working temperature : -30° C --50° C / IP67 Waterproof / 50,000Hrs Lifespan / 5 years warranty						

FL-series application



Indoor outdoor sport field courts, play ground, highway, high mast, airport, seaport, park, square, advertising board, landscape.



### T-Series Light Distribution Curve



### T-series features



#### Continuous Stacked Fin Technology

Gear slotting fins provide perfect contact between fins and the conductivity panels to ensure the best heat transfer.

Two ventilation channels of specially designed. Heatsink fins will take the heat away from the LED bottom and dissipate away rapidly.



### FL100-300WT



#### T-series items

Item No.	LAL-FL-300WT	LAL-FL-250WT	LAL-FL-200WT	LAL-FL-150WT	LAL-FL-100WT
Power	300W	250W	200W	150W	100W
Input Voltage	100-277V / 180-528VAC 50/60Hz				
Beam angle	15° / 30° / 60° / 90° / 120°				
CCT	2700K/3000K / 4000K / 5000K / 5700K / 6500K				
Dim	1-10V / Dali / PWM dimmable				
Surge Protection	SPD 20KV/10KV/6KV/4KV				
Driver /LEDs	Meanwell / Sosen / Inventronics ; Lumileds SMD3030 / CITIZEN COB ; Ra70/Ra80/Ra90				
Materials	Fin aluminum heat sink + built in copper pipe				
Light efficiency	130lm/W				
Spec.	Working temperature : -3° C --50° C / IP67 Waterproof / 50,000Hrs Lifespan / 5 years warranty				

#### T-series application

Indoor outdoor sport field courts, playgrounds, highway, high mast, airport, seaport, park, square, advertising board.

