

SOLAR LED STREET LIGHT QUOTATION SHEET

| Item | Q'ty | Unit price EX Works USD | Parameters | Size & Packages |
|--|---------|-------------------------------|---|--|
|  <p>LAL-SSL-30W</p> | <10pcs | \$216.34 | Material:aluminum Alloy Solar Panel:18V 30W (High efficiency imported Mono silicon solar cell) Led : Lumileds SMD3030 CCT: 2700K -6500K Battery:Lithium 12V/12AH Install height: 3-5M Lumens efficiency: 180-210Lm/W Operating mode: Time control / Induction control / Time & induction control | Lamp size: 680*295*44mm Carton Size:785*350*190mm Gross Weight: 7.8KG |
| | >100pcs | \$212.66 | | |
| | >500pcs | \$188.28 | | |
| | | | | |
|  <p>LAL-SSL-40W</p> | <50pcs | \$245.66 | Material:aluminum Alloy Solar Panel:18V 35W (High efficiency imported Mono silicon solar cell) Led : Lumileds SMD3030 CCT: 2700K -6500K Battery:Lithium 12V/16AH Install height: 3-5M Lumens efficiency: 180-210Lm/W Operating mode: Time control / Induction control / Time & induction control | Lamp size: 920*295*44mm Carton Size: 930*350*190mm Gross Weight: 9.6KG |
| | >50pcs | \$242.00 | | |
| | >300pcs | \$214.26 | | |
| | | | | |
|  <p>LAL-SSL-60W</p> | <50pcs | \$308.00 | Material:aluminum Alloy Solar Panel:18V 50W (High efficiency imported Mono silicon solar cell) Led : Lumileds SMD3030 CCT: 2700K -6500K Battery:Lithium 12V/18AH Install height: 5-6M Lumens efficiency: 180-210Lm/W Operating mode: Time control / Induction control / Time & induction control | Lamp size: 1136*295*44mm Carton Size: 1180*345*1900mm Gross Weight: 13.6KG |
| | >50pcs | \$304.34 | | |
| | >300pcs | \$269.44 | | |
| | | | | |
|  <p>LAL-SSL-80W</p> | <50pcs | \$319.00 | Material:aluminum Alloy Solar Panel:18V 50W (High efficiency imported Mono silicon solar cell) Led : Lumileds SMD3030 CCT: 2700K -6500K Battery:Lithium 12V/20AH Install height: 6-7M Lumens efficiency: 180-210Lm/W Operating mode: Time control / Induction control / Time & induction control | Lamp size: 1136*295*44mm Carton Size: 1180*345*190mm Gross Weight: 14KG |
| | >50pcs | \$315.34 | | |
| | >300pcs | \$279.18 | | |
| | | | | |
|  <p>LAL-SSL-100W</p> | <50pcs | \$429.00 | Material:aluminum Alloy Solar Panel:18V 75W (High efficiency imported Mono silicon solar cell) Led : Lumileds SMD3030 CCT: 2700K -6500K Battery:Lithium 12V/32AH Install height: 9-12M Lumens efficiency: 180-210Lm/W Operating mode: Time control / Induction control / Time & induction control | Lamp size: 1136*420*44mm Carton Size: 1135*490*950mm Gross Weight: 18.5KG |
| | >50pcs | \$425.34 | | |
| | >300pcs | \$376.58 | | |
| | | | | |
|  <p>LAL-SSL-120W</p> | <50pcs | \$584.84 | Material:aluminum Alloy Solar Panel:18V 110W (High efficiency imported Mono silicon solar cell) Led : Lumileds SMD3030 CCT: 2700K -6500K Battery:Lithium 12V/50AH Install height: 9-12M Lumens efficiency: 180-210Lm/W Operating mode: Time control / Induction control / Time & induction control | Lamp size: 1460*420*44mm Carton Size: 1530*100*480mm Gross Weight: 19.2KG |
| | >50pcs | \$581.16 | | |
| | >300pcs | \$514.56 | | |
| | | | | |

- 1, CCT: warm white:2700K / 3000K; Natual white:4000K Day white: 5000K; Cool white: 5700K / 6500K;
- 2, Payment terms: PAYPAL, Western Union, T/T, Money Gram. 40% deposit, 60% balance before shipping;
- 3, Unit price is based on EX work, lead time: samples 5-7 days, bulk order: 7-15 days; Shipping way: Express, Air, Sea option, Clients's own shipping;
- 4, CE, 2 years warranty.

Features

- 1) Smart control with PIR sensor; Without any electricity and wires;
- 2) Long lasting: 3 working days without sunshine;
- 3) SMD3030 LEDs. 210m/W high efficiency;
- 4) High efficiency imported silicon solar cell;
- 5) High performance Lithium battery ;



Press the on/off button to activate the fixture.



Fasten the screws to finish the installation on the pole.




When the light is above 10lux, it will turn off the light automatically, solar panel starts to charge.




1. Light switch auto-off for sun charging in daytime



2. It will gradually auto turn on bright at night



3. Sensor working distance is from 7 to 10 meters, when people get near, the lamp will automatically become brighter



4. When people walk away 5-8m, the lamp will automatically dim back to former brightness.

